



Shanghai Green Tech Co.,Ltd.

GTCAP



Table2 Rated Voltage,derated voltage, capacitance, case code and dissipation factor

Rated Volatge U _R (V)	Derated Voltage U _C (V)	Case code	Cap. C _R (μF)	tg (%) DF 25	Rated Voltage U _R (V)	Derated Voltage U _C (V)	Case code	Cap. C _R (μF)	tg (%) DF 25
25 ,85	125 200				25 ,85	125 200			



Shanghai Green Tech Co.,Ltd.



How to order

(Part No.: GTCA53D 477 K 0255)

GT	CA53D	477	K	025	5
Brand Name	Type	Capacitance	Tolerance	Rated voltage /DC	Case code

Green Tech
Silver case
hi-temp. Wet
Tantalum
Capacitor

477 47X10⁷(pF)This is
express74 05 ef TDs is

Notes

- 1 Tantalum capacitors can't been measured by multimeter (Easily cause irreversible damage and lead to reject)
- 2 Capacitance, DF measure frequency: 100Hz $U_{\text{eff}}=2.2^{0.1,0}V$ $U_{\text{eff}}=1.0^{0.5}V$ (effective value)
- 3 Measure leakage current above 85 ,please use derated voltage.
- 4 Special size and big capacitance products, please negotiate with us